

A328

GLOSSY POLYPROPYLENE LABEL

Description

A 90 micron high gloss coated polypropylene film, laminated with a high tack modified aqueous acrylic adhesive to a glassine liner.

Material Coated polypropylene

Finishing Glossy

Color White / Transparent

Adhesive High tack

Liner Glassine liner

Service temperature -20 to 70 °C

Physical data

High quality gloss coated film suitable for inkjet printing. This film exhibits instant drying and good water and smudge resistance. End uses include domestic and retail labelling. End user testing is required to confirm suitability of all components in end use application.

Face	Unit	Typical value	Test method
Substance	GSM	75 ± 8%	TAPPI 410
Caliper	Micron	90 ± 8%	TAPPI 411

Adhesive	Unit	Typical value	Test method
Peel adhesion	N/25mm	14 to glass	FINAT 1
Loop tack	N/25mm	10 to glass	FINAT 9
Service temp	°C	-20 to 70 °C	----
Application temp	°C	-10 °C	----

Partly transparent

With certain labels, A328 is partly transparent. This transparent material is a clear glossy polymeric plasticised vinyl film. The adhesive is a strong, permanent, solvent-based acrylic.

Liner

62 gram white glassine liner suitable for use where there is automatic label registration or dispensing.

Storage

Two years under storage conditions as defined by FINAT (20-25°C; 40-50%RH)

Disclaimer:

Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available as is and that Altec gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.