

A337

TOUGHSURFACE FLEXTREME

Description

This single sided tape consists of a polyester film carrier and a hotmelt synthetic rubber adhesive. It has a very good tack and adhesion to rough or irregular surfaces. Good adhesion to LSE substrates.

Material	PET	Temperature	60 °C
Finishing	Glossy	Applications	General purpose single sided tape
Color	White	Print technology	Thermal transfer
Adhesive	Rubber synthetic	Ribbon(s)	AR-10 / AR-01
Liner	Paper white		

Physical data

Thickness carrier	0,05 mm	1,97 Mils
Thickness total	0,285 mm	11,2 Mils
Adhesion on stainless steel	27 N/25mm	6,17 Lbs/inch
Tensile strength length	80 N/25mm	18,3 Lbs/inch
Elongation length	15 %	
Temperature performance	60 °C	140 °F

Storage

1 year shelf life whilst stored in original packaging and ambient room temperature. Keep out of direct sunlight.

Application tips

All substrates should be clean and contamination free, a solvent such as Isopropyl-Alcohol is recommended for cleaning purposes, and the tape should be applied with pressure.

Disclaimer:

Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available as is and that Altec gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.